



Technical Data
 Material:
 Pin(outer sleeve): Brass, machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated: 2μm/80μ"Ni, 5μm/200μ"Sn
 Gold Plated: 2μm"/80μ"Ni, 0.8μ" gold
 Insulator: PPS UL94V-0

Electrical:
 Current rating: 3Amps/contact max.
 Contact resistance: ≤ 4mΩ/contact
 Insulation resistance: ≥ 1000MΩ at V=100V
 Operating voltage: 60VAC/DC

Mechanical:
 Operating temperature: -40 ° C to +105 ° C
 Soldering temperature: +255 ° C
 Critical Dimensions: (*)

ECN NO.	REV.	DATE.	DESCRIPTION.
	A		NEW
			CHANGE.
			CHECK.
			APPRO.

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP28-0762W-2XNP-1220A
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE		30~以上	±0.30	ANGLE
	10~30	±0.20		±2°
	5~10	±0.15		
	~ 5	±0.10		



深圳市联丰电子有限公司
 SHENZHEN LINFENGYING ELECTRONIC CO.,LTD