



Ordering Information & Dimensions

PART NO.	Dimensions		PART NO.	Dimensions	
	A	B		A	B
03P	2.54	3.81	18P	21.59	22.86
04P	3.81	5.08	19P	22.86	24.13
05P	5.08	6.35	20P	24.13	25.40
06P	6.35	7.62	21P	25.40	26.67
07P	7.62	8.89	22P	26.67	27.94
08P	8.89	10.16	23P	27.94	29.21
09P	10.16	11.43	24P	29.21	30.48
10P	11.43	12.70	25P	30.48	31.75
11P	12.70	13.97	26P	31.75	33.02
12P	13.97	15.24	27P	33.02	34.29
13P	15.24	16.51	28P	34.29	35.56
14P	16.51	17.78	29P	35.56	36.83
15P	17.78	19.05	30P	36.83	38.10
16P	19.05	20.32	31P	38.10	39.37
17P	20.32	21.59	32P	39.37	40.64

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 5000MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass/Gold-flash
 Material: Nylon 6T,UL94V-0
 Color: Natural(Black)

Optional Dim. available but MOQ requested

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

APPROVALS		DATE	TITLE:	
DRAWN	ZHIWEI.CHEN	2015.07.07	PART NO.	GP26-1270WV-NP
CHECKED			UNIT: mm	SCALE: 1:1
APPROVALS			DRAWING NO.	PROJ:
TOLERANCES ARE				SHEET 1 OF 1
30~以上	±0.30	ANGLE		
10~30	±0.20			
5~10	±0.15			
~ 5	±0.10	±2°		



深圳市联丰电子有限公司
 SHENZHEN LINFENYING ELECTRONIC CO.,LTD