



PCB Layout Diagram
Top View

3	TERMINAL (-)	1	PHOSPHOROUS BRONZE, T=0.15MM	Sn-Plating
2	TERMINAL (+)	1	PHOSPHOROUS BRONZE, T=0.15MM	Sn-Plating
1	HOUSING	1	LCP	WHITE
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR
	A		NEW	
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.

APPROVALS	DATE	TITLE:	PART NO.	SCALE:	PROJ.
DRAWN	ZHIWEI.CHEN	2015.07.07	GP07-CR2032-03	1:1	PROJ.
CHECKED					
APPROVALS					
TOLERANCES ARE		30 ^{UM} 以上	±0.30	ANGLE	UNIT: mm
		10~30	±0.20		SCALE: 1:1
		5~10	±0.15	±2°	PROJ.
		~ 5	±0.10		SHEET 1 OF 1

NOTE:

1. MATERIAL:

- a. HOUSING: THERMOPLASTIC GLASS FIBRE UL94V-0
- b. CONTACT: PHOSPHOR BRONZE (SURFACE PLATING: Sn100u")

SEE ORDERING INFORMATION

2. ELECTRIC:

- a. CONTACT RESISTANCE: 30 MILLIOHMS MAX
- b. INSULATION RESISTANCE: 1000 MEGA OHMS MIN
- c. DIELECTRIC VOLTAGE: 500V AC ONE SEC LEVEL
- d. OPERATING TEMPERATURE: -25~C~+85~C